



SAFE, INTELLIGENT AND EASY TO OPERATE

APX™ 6500 PROJECT 25 MOBILE RADIO

We've put exceptional flexibility into the advanced APX™ 6500 P25 mobile radio. We made it easy to operate and easy to use. Choose between 4 control heads, mid- and high-power models and multiple installation configurations – all of which are easy to set up. Safety features such as GPS location tracking, intelligent lighting and one-touch controls keep first responders safer than ever before.

FLEXIBLE PLATFORM

- Interchangeable control heads that best support your operational needs: 02, 03, 05, 07 and 09
- 2 transceiver options: high-power and mid-power
- Dual-control head support offered on the 02, 05, 07, 09

EASY TO SET UP AND USE

- Mid-power model fits into any existing XTL™ footprint, so you can reuse mounting holes and cables
- High-power model trunnion design lets you remove the radio without removing the cables
- 12-character RFID label helps you track information without uninstalling your radio

CUTTING-EDGE TECHNOLOGY AND ADVANCED FEATURES

- Project 25 Phase 2 technology provides twice the voice capacity
- Integrated GPS lets you locate and track an individual or vehicle
- Advanced features like intelligent lighting, radio profiles and text messaging improve communication and coordination



APX™ 6500 SPECIFICATIONS

FEATURES AND BENEFITS:

Available in 700-800 MHz, VHF, UHF Range 1 and UHF Range 2 bands
Channels: 870*
Trunking standards supported:

- Clear or digital encrypted Trunked Operation
- Capable of SmartZone®, SmartZone Omnilink, SmartNet®

 Analog MDC-1200 and Digital APCO P25 Conventional System Configurations
 Narrow and wide bandwidth digital receiver (6.25 kHz equivalent / 12.5 kHz / 30 kHz / 25 kHz)
 Embedded digital signalling (ASTRO & ASTRO 25)
 Integrated GPS capable
 Integrated encryption hardware
 Intelligent lighting
 Radio profiles
 Unified call list

Ships standard IP54
 Utilises Windows XP, Vista and Windows 7 Customer Programming Software (CPS)

- Supports USB communications
- Built in FLASHport™ support

 Reuse of most XTL™ accessories plus new IMPRES accessories

OPTIONAL FEATURES:

Enhanced encryption software options
 Programming Over Project 25 (POP25)
 Text messaging
 Over the Air Rekeying (OTAR)
 12-character RF ID asset tracking
 Tactical OTAR
 Siren and light interface module

Enhancement package available*

TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS

	700 MHz		800 MHz		VHF		UHF Range 1		UHF Range 2	
Frequency Range/Bandsplits	764-776 MHz 794-806 MHz		806-824 MHz 851-870 MHz		136-174 MHz		380-470 MHz		450-520 MHz	
Channel Spacing	25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz	
Maximum Frequency Separation	Full Bandsplit		Full Bandsplit		Full Bandsplit		Full Bandsplit		Full Bandsplit	
Rated RF Output Power Adj [†]	10-30 Watts		10-35 Watts		10-50 Watts or 25-110 Watts		10-40 Watts or 25-110 Watts		10-45 Watts (450-485 MHz) 10-40 Watts (485-512 MHz) 10-25 Watts (512-520 MHz)	
Frequency Stability [*] (-30°C to +60°C; +25°C Ref.)	±0.00015 %		±0.00015 %		±0.0002 %		±0.0002 %		±0.0002 %	
Modulation Limiting [*]	±5 kHz / ±2.5 kHz		±5 kHz/±4 kHz (NPSAPC) /±2.5 kHz		±5 kHz / ±2.5 kHz		±5 kHz / ±2.5 kHz		±5 kHz / ±2.5 kHz	
Modulation Fidelity (C4FM) 12.5kHz Digital Channel	±2.8 kHz		±2.8 kHz		±2.8 kHz		±2.8 kHz		±2.8 kHz	
Emissions [*]	Conducted+ -75/-85 dBc	Radiated+ -20/-40 dBm	Conducted -75 dBc	Radiated -20 dBm	Conducted -85 dBc	Radiated -20 dBm	Conducted -85 dBc	Radiated -20 dBm	Conducted -85 dBc	Radiated -20 dBm
Audio Response [*]	+1, -3 dB (EIA)		+1, -3 dB (EIA)		+1, -3 dB (EIA)		+1, -3 dB (EIA)		+1, -3 dB (EIA)	
FM Hum & Noise 25 kHz 12.5 kHz	-50 dB -48 dB		-50 dB -48 dB		-53 dB -52 dB		-53 dB -50 dB		-53 dB -50 dB	
Audio Distortion [*]	2 %		2 %		2 %		2 %		2 %	

DIMENSIONS

		Inches	Millimeters
Mid Power Radio Transceiver		2 x 7 x 8.6	50.8 x 177.8 x 218.4
O5 Control Head		2 x 7 x 2.5	50.8 x 180.3 x 63.5
O2 Control Head		2.7 x 8 x 2.1	68.4 x 206 x 52.83
O7 Control Head		2 x 7 x 1.5	50.8 x 178 x 40
Mid Power Radio Transceiver and O5 Control Head–Dash Mount		2 x 7 x 9.6	50.8 x 180.3 x 243.8
Mid Power Radio Transceiver and O2 Control Head - Dash Mount		2.7 x 8 x 10.5	68.4 x 206 x 268
Mid Power Radio Transceiver and O7 Control Head - Dash Mount		2 x 7 x 10.3	50.8 x 178 x 262
Mid Power Radio Transceiver and Remote Mount		2.0 x 7 x 9.6	50.8 x 180.3 x 243.8
High Power Radio Transceiver		2.9 x 11.5 x 8.8	74 x 293 x 223
High Power Radio Transceiver with Handle		3.4 x 11.5 x 8.8	87 x 293 x 223
Mid Power Radio Transceiver and O5 Control Head Weight		6.6 lbs	3.0 kg
Mid Power Radio Transceiver and O2 Control Head Weight		7.12 lbs	3.23 kg
Mid Power Radio Transceiver and O7 Control Head Weight		6.74 lbs	3.06 kg
High Power Radio Transceiver Weight	With Trunnion	14.2 lbs	6.4 kg
	Without Trunnion	12 lbs	5.4 kg

APX 6500 CONTROL HEAD PORTFOLIO



02 RUGGED CONTROL HEAD

- Large color display with intelligent lighting
- 3 lines of text 14 characters max / 1 line of icons / 1 line of menus
- Built in 7.5 watt speaker
- Multiple control head configuration (up to 2)
- Multifunction volume/channel knob
- Night/day mode button



03 HAND HELD CONTROL HEAD

- Large color display with intelligent lighting
- 2 lines of text 14 characters max / 1 line of icons / 1 line of menus
- Integrated full size DTMF keypad
- Hand-held control head with intuitive user interface
- Two quick-access side buttons
- Display contrast selector



05 STANDARD CONTROL HEAD

- Tri-color display with intelligent lighting
- 2 lines of text 14 characters max / 1 line of icons / 1 line of menus
- Available with Keypad Microphone
- Multiple control head configuration (up to 2)
- Display contrast selector



07 ENHANCED CONTROL HEAD

- Large color display with intelligent lighting
- 3 lines of text 14 characters max / 1 line of icons / 1 line of menus
- Available with Lighting & Siren Controls or DTMF Keypad
- Multiple control head configuration (up to 2)
- Multifunction volume/channel knob
- Night/day mode button



09 INTEGRATED CONTROL HEAD

- Extra-large full color display with intelligent lighting
- 2 lines of text 14 characters max / 1 line of icons / 1 line of menus
- Integrated full size DTMF keypad
- Large programmable one-touch buttons
- Dedicated siren controls
- Integrated Response Selector
- Night/day mode button

RECEIVER – TYPICAL PERFORMANCE SPECIFICATIONS

	700 MHz	800 MHz	VHF	UHF Range 1		UHF Range 2	
Frequency Range/Bandsplits	764-776 MHz	851-870 MHz	136-174 MHz	380-470 MHz		450-520 MHz	
Channel Spacing	25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz		25/20/12.5 kHz	
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit		Full Bandsplit	
Audio Output Power at 3% distortion*	7.5 W or 15 W ++	7.5 W or 15 W ++	7.5 W or 15 W ++	7.5 W or 15 W ++		7.5 W or 15 W ++	
Frequency Stability* (-30°C to +60°C; +25°C Ref.)	+/-0.8 PPM		+/-0.8 PPM	+/-0.8 PPM		+/-0.8 PPM	
Analog Sensitivity* 12 dB SINAD	-121 dBm	-121 dBm	Pre-Amp -123 dBm	Standard -119 dBm	Pre-Amp -123 dBm	Standard -119 dBm	Pre-Amp -123 dBm
Digital Sensitivity 5% BER	-121.5 dBm	-121.5 dBm	-123 dBm	-119 dBm	-123 dBm	-119 dBm	-123 dBm
Intermodulation 25 kHz	82 dB	82 dB	84 dB	86 dB	82 dB	86 dB	82 dB
12.5 kHz	82 dB	82 dB	85 dB	86 dB	83 dB	85 dB	83 dB
Spurious Rejection	91 dB	91 dB	95 dB	93 dB		93 dB	
Audio Distortion at rated*	1.20%	1.20%	1.20%	1.20%		1.20%	
FM Hum & Noise 25 kHz	59 dB	59 dB	59 dB	55 dB	57 dB	50 dB	50 dB
12.5 kHz	50 dB	50 dB	50 dB	50 dB	50 dB	50 dB	50 dB
Selectivity* 25 kHz	85 dB	85 dB	85 dB	85 dB	85 dB	85 dB	85 dB
12.5 kHz	75 dB	75 dB	75 dB	75 dB	75 dB	75 dB	75 dB
30 kHz	—	—	90 dB	—	—	—	—

SIGNALING (ASTRO MODE)

Signaling Rate	9.6 kbps
Digital ID Capacity	10,000,000 Conventional / 48,000 Trunking
Digital Network Access Codes	4,096 network site addresses
ASTRO® Digital User Group Addresses	4,096 network site addresses
Project 25 – CAI Digital User Group Addresses	65,000 Conventional / 4,094 Trunking
Error Correction Techniques	Golay, BCH, Reed-Solomon codes
Data Access Control	Slotted CSMA: Utilizes infrastructure-sourced data status bits embedded in both voice and data transmissions.

GPS SPECIFICATIONS

Channels	12
Tracking Sensitivity	-153 dBm
Accuracy**	<10 meters (95%)
Cold Start	<60 seconds (95%)
Hot Start	<10 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted) GPS

PRODUCT SPEC SHEET
APX™ 6500

POWER AND BATTERY DRAIN						
Model Type	136-174 MHz, 380-470 MHz, 450-520 MHz, 764-870 MHz					
Minimum RF Power Output	10-35 Watt (764-870 MHz), 10-50 Watts or 25-110 Watts (136-174 MHz), 10-40W or 25-110 Watts (380-470 MHz), 10-45Watts (450-485 MHz), 10-40Watts (485-512 MHz), 10-25Watts (512-520 MHz)					
Operation	13.8V DC ±20% Negative Ground					
Standby at 13.8V	0.85A (764-870 MHz), 0.85A (136-174 MHz), 0.85A (380-470 MHz), 0.85A (450-520 MHz)					
Receive Current at Rated Audio at 13.8V	3.2A (764-870 MHz), 3.2A (136-174 MHz), 3.2A (380-470 MHz), 3.2A (450-520 MHz)					
Transmit Current (A) at Rated Power	136-174 MHz (10-50 Watt) 380-470 MHz (10-40 Watt) 380-470 MHz (10-40 Watt)	13A (50W) 11A (40W) 11A (45W)	8A (15W) 8A (15W) 8A (15W)	764-870 MHz (10-35 Watt) 136-174 MHz (25-110 Watt) 380-470 MHz (25-110 Watt)	12A (50W) 20A (110W) 24A (110W)	8A (15W)

MOBILE MILITARY STANDARDS 810 C, D, E , F & G										
	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I-A1, II
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I-C3, II
Temperature Shock	503.1	1 Proc	503.2	I/A1C3	503.3	I/A1C3	503.4	I	503.5	I-C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I-A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II-Aggravated
Salt Fog	509.1	1 Proc	509.2	1 Proc	509.3	1 Proc	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I, II	510.3	I, II	510.4	I, II	510.5	I, II
Vibration	514.1w	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I-cat.24
Shock	516.2	I, III, V	516.3	I, V, VI	516.4	I, V, VI	516.5	I, V, VI	516.6	I, V, VI

ENCRYPTION	
Supported Encryption Algorithms	ADP, AES, DES, DES-XL, DES-OFB, DVP-XL
Encryption Algorithm Capacity	8
Encryption Keys per Radio	Module capable of storing 1024 keys. Programmable for 64 Common Key Reference (CKR) or 16 Physical Identifier (PID)
Encryption Frame Re-sync Interval	P25 CAI 300 mSec
Encryption Keying	Key Loader
Synchronization	XL – Counter Addressing, OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology(NIST) approved random number generator
Encryption Type	Digital
Key Storage	Tamper protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-2 Level 3 FIPS 197

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-30°C / +60°C
Storage Temperature	-40°C / +85°C
Humidity	Per MIL-STD
ESD	IEC 801-2 KV
Water and Dust Intrusion	IP54, MIL-STD

FCC TYPE ACCEPTANCE ID		
BAND	OUTPUT POWER	TRANSMITTER NUMBER
764-870 MHz	10-35 Watts	AZ492FT5858
136-174 MHz	25-110 Watts	AZ492FT3821
136-174 MHz	10-50 Watts	AZ492FT3824
380-470 MHz	10-40 Watts	AZ492FT4894
380-470 MHz	25-110 Watts	AZ492FT4897
450-520 MHz	10-45 Watts	AZ492FT4896

* Measured in the analog mode per TIA/EIA 603 under nominal conditions
** Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength)
+ Specs includes performance for the non-GNSS/GNSS bands
++ Output power in to 8 and 3.2 Ohm external speakers respectively

Specifications subject to change without notice.
All specifications shown are typical.
Radio meets applicable regulatory requirements.

PRODUCT SPEC SHEET
APX™ 6500

REGULATORY COMPLIANCE

Radio (R&TTE Article 3.2)	Directive 1999/5/EC RTTE EN 300 086-2 v1.3.1
	EN 300 113-2 v1.5.1
EMC (R&TTE Article 3.1.b)	EN 301 489-1 V1.9.2
	EN 301 489-5 V1.3.1
	EN 300 086-2 v1.3.1 (rad. emissions)
Electrical Safety (R&TTE Article 3.1.a)	EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + AC:2011
	ICNIRP(1998) Occupational Controlled Environment
Environmental	Directive 2002/96/EC WEEE
	Directive 2011/65/EU RoHS-2
Year of first application of CE Mark	2012 (136-174MHz) ; 2012 (380-470MHz)
Type Designator	MMB305P (136-174MHz) ; MMB505P (380-470MHz)
Automotive	E-mark, 72/245/EEC and 2004/104/EC as amended by 2009/19/EC
Automotive Marking	e 24 03 2044

Motorola Solutions UK Limited, Jays Close, Viabes Industrial Estate, Basingstoke, Hampshire RG22 4PD motorolasolutions.com

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2015 Motorola Solutions, Inc. All rights reserved.

R3-1-2047F/(EA)